

ICF-11

MERV 11, 100% Cellulose filter media.



ICF-11

is a proprietary 100% cellulose filter media with excellent resistance to moisture and high particulate release characteristics.

A low inital resistance to airflow and MERV 11 efficiency rating combine for an ideal filter for a wide variety of applications.

Specifications	
Basis Weight (lbs/ft².)	76lbs/3000ft ²
Caliper	28 mils @ 2.7 psi
Air Permeability	25 cfm/ft ² @ 0.5 wc
Resin Content	18%
Mullen Burst Dry	70 psi
Mullen Burst Wet	50 psi
Resin System	Non-Phenolic

Test Results		
Airflow Rate (CFM)	500	
Initial Resistance (in WG)	0.59	
E1 (%) Initial Efficiency 0.30-1.0 um	35%	
E2 (%) Initial Efficiency 1.0-3.0 um	71%	
E3 (%) Initial Efficiency 3.0-10.0 um	97%	
MERV Rating	11	

Applications

Gas Turbine Inlet Filters

Abrasive Blasting

Dry Chemical Processing

Sand Blasting

Mining

8401 Air Commerce Drive, Louisville KY 40219 | toll free: 800.757.5624 | phone: 502.634.4796 | Fax: 502.969.2364 info@kochfilter.com | www.kochfilter.com