

Duo-Pak 40™

Extended Surface Self-Seal
Two Pocket Filter



Duo-Pak 40 filters are designed for applications where long service life with a medium efficiency filter is required.

The **Duo-Pak 40**, 2 ply configuration, with the benefits of the depth-loading characteristics of 550 media, offers high dust holding capacity and efficiency. The progressive density design of the 550 media is enhanced with a specially formulated tackifier to prevent particle migration and provide exceptional efficiency above five microns.

The **Duo-Pak 40**, 1 ply configuration, which utilizes a tackified single density polyester media, offers an economical alternative for applications where high dust holding capacity in a primary filter is required.

The self-sealing feature of the **Duo-Pak 40** prevents air bypass and eliminates the need for clips; saving time and money during change-outs. The longer service life and low cost make the Duo-Pak 40 an ideal replacement for four-inch, or six-inch pleat applications where holding frames, or flat bank side access housings are in use.

Nominal Size	Media Sq. Ft.	Capacity @500 CFM	1-Ply MERV 7			2-Ply MERV 8	
			Initial Resistance (w.g.)			Initial Resistance (w.g.)	
			@300 FPM	@500 FPM	Capacity @500 CFM	@300 FPM	@500 FPM
16x20x15	11.4	1115	0.10	0.13	1115	0.09	0.15
16x25x15	13.4	1400	0.10	0.13	1400	0.09	0.15
20x20x15	12.2	1400	0.10	0.13	1400	0.09	0.15
20x25x15	14.3	1740	0.10	0.13	1740	0.09	0.15
20x24x15	13.9	1675	0.10	0.13	1675	0.09	0.15
12x24x15	12.2	1200	0.10	0.13	1200	0.09	0.15
24x24x15	14.7	2000	0.10	0.13	2000	0.09	0.15
16x20x10	7.6	1115	0.12	0.17	1115	0.13	0.19
16x25x10	9.0	1400	0.12	0.17	1400	0.13	0.19
20x20x10	8.1	1400	0.12	0.17	1400	0.13	0.19
20x25x10	9.5	1740	0.12	0.17	1740	0.13	0.19
20x24x10	9.2	1675	0.12	0.17	1675	0.13	0.19
12x24x10	8.1	1200	0.12	0.17	1200	0.13	0.19
24x24x10	9.8	2000	0.12	0.17	2000	0.13	0.19

