

BioMAX™ 95.00%



FEATURES:

- Individually Tested Standard Capacity Media
- Particle Board & Galvanized Steel Cell Sides

DESCRIPTION: HEPA grade filter with standard capacity media.

APPLICATIONS: Air handlers in medical facilities, pharmaceuticals, clean room manufacturing and indoor gun ranges.

EFFICIENCY: 95% at 0.3μ

MEDIA: Submicron glass fibers formed into a water-resistant, high efficiency high density, wet-laid paper mat.

RECOMMENDED FINAL PRESSURE DROP: Consult factory. Rule of thumb is change filter when the initial pressure drop doubles.

TEMPERATURE: Maximum continuous operating temperature 180°F (82°C)

RATINGS: UL Rated

PRICE PAGE: L1-4

See Bulletin No. K-603A for more details

Actual Size W x H x D	Koch Part #	Airflow Capacity (CFM)	Initial Resistance (inches W.G.)	Media Area (sq. ft.)	Efficiency	Shipping Weight (lbs)
Style SBW - Particle Board Cell Sides						
24x24x11.50	H66G7X1	1000	1.0	154	95.00 @ 0.3 Micron	40
23.38x23.38x11.50	H64G7X1	950	1.0	145	95.00 @ 0.3 Micron	38
24x12x11.50	H62G7X1	500	1.0	67	95.00 @ 0.3 Micron	33
12x12x11.50	H61G7X1	250	1.0	32	95.00 @ 0.3 Micron	15
24x18x11.50	H63G7X1	750	1.0	100	95.00 @ 0.3 Micron	33
24x30x11.50	H68G7X1	1250	1.0	172	95.00 @ 0.3 Micron	46
24x24x5.88	H16G7X1	500	1.0	79	95.00 @ 0.3 Micron	23
24x12x5.88	H12G7X1	250	1.0	37	95.00 @ 0.3 Micron	24
Style SBM - Galvanized Steel Cell Sides						
24x24x11.50	H66A7X1	1000	1.0	154	95.00 @ 0.3 Micron	40
23.38x23.38x11.50	H64A7X1	950	1.0	145	95.00 @ 0.3 Micron	38
24x12x11.50	H62A7X1	500	1.0	67	95.00 @ 0.3 Micron	33
12x12x11.50	H61A7X1	250	1.0	32	95.00 @ 0.3 Micron	15
24x18x11.50	H63A7X1	750	1.0	100	95.00 @ 0.3 Micron	33
24x30x11.50	H68A7X1	1250	1.0	172	95.00 @ 0.3 Micron	46
24x24x5.88	H16A7X1	500	1.0	79	95.00 @ 0.3 Micron	23
24x12x5.88	H12A7X1	250	1.0	37	95.00 @ 0.3 Micron	24

Notes:

- All BioMAX HEPA HC filters are furnished with one gasket on the downstream side. If additional gaskets are needed, state location when ordering.
- Contact factory for sizes not listed above. A customer drawing or written submittal is required on all special sizes.
- BioMAX HEPA HC Style SBM for High Temperature applications are available.