



BioMAX™ 95.00% FM Single Header

FEATURES:

- Individually Tested Standard Capacity Media
- 26 Gage Galvanized Steel Cell Sides
- Single Header

DESCRIPTION: HEPA grade filter with standard capacity media.

APPLICATIONS: Air handlers in medical facilities, pharmaceuticals, clean room manufacturing and indoor gun ranges.

EFFICIENCY: 95% at 0.3μ

MEDIA: Submicron glass fibers formed into a water-resistant, high efficiency high density, wet-laid paper mat.

RECOMMENDED FINAL PRESSURE DROP: Consult factory. Rule of thumb is change filter when the initial pressure drop doubles.

TEMPERATURE: Maximum continuous operating temperature 180°F (82°C)

RATINGS: UL Rated

PRICE PAGE: L1-4A

See Bulletin No. K-603A for more details

Actual Size W x H x D	Koch Part #	Airflow Capacity (CFM)	Initial Resistance (inches W.G.)	Media Area (sq. ft.)	Efficiency	Shipping Weight (lbs)
24x24x11.50	H66K7X4	1000	1.0	282	95.00 @ 0.3 Micron	40
23.38x23.38x11.50	H64K7X4	950	1.0	275	95.00 @ 0.3 Micron	38
11.38x23.38x11.50	H60K7X4	475	1.0	122	95.00 @ 0.3 Micron	33

Notes:

- All BioMAX 95 HEPA filters are furnished with one gasket on the downstream side. If additional gaskets are needed note the location when ordering.
- Contact factory for sizes not listed above. A customer drawing or written submittal is required for all special size filters.
- BioMAX 95 HEPA Style for High Temperature applications are available.