

LM6000

Static Gas Turbine Air Inlet Air Filter



FEATURES

Long filter lifecycle

Low replacement and maintenance cost

Eliminated downstream dust and fiber shedding

Low resistance to airflow increases energy savings

Eliminates corrosion and rust

Designed for high moisture and humidity

LM6000

Koch Filter has earned air filtration industry recognition as a world leader aftermarket supplier of gas turbine inlet air filters. Our filters have been successfully installed in thousands of GT operations worldwide.

You'll find our filters in all environments, even the harshest and challenging. Innovative product introductions, ISO 9001 manufacturing facilities, application-specific solutions and extensive field and laboratory filter testing gives Koch a unique advantage over other suppliers.

Designed to fit: GE[®] LM6000 housings with blended wet laid or all synthetic media available to meet your requirements.

Media Options

| | |
|---------|---|
| ICF 12 | High Efficiency Cellulose/Synthetic Premium Media Blended cellulose/synthetic premium media with a non-phenolic resin system. High hydrophobicity (moisture resistance), excellent capacity and cake release characteristics. |
| ICF 12S | High Efficiency Premium Blend of Synthetic Media Blended polyester/glass premium media with a vinyl chloride resin system. One of the highest moisture resistance media on the market, great cake release and media strength. |
| ICF 15 | Nano Fiber Coating Blended cellulose/polyester paper media with Nano Fiber. High moisture resistance, excellent capacity and cake release. MERV 15 rating makes it ideal for use in pulse systems. |
| ICF 16 | High Efficiency Electro spun Nano Fiber Media Blended cellulose/polyester paper filter media with Nano Fiber, a no cure acrylic resin system. MERV 16 rating with high moisture resistance. |