

Flat Bank ASHRAE Housing

Side Access Flat Bank Housing for ASHRAE Rated Filters



FEATURES

Available for single or multi-stage prefiltration

All tracks and doors are fully gasketed

Galvanized or stainless steel construction

Welded and caulked construction

Upstream corners gussets for rigidity

Quick access doors

Holding Frames and Fasteners are not required

Built for systems up to $\pm 3''$ W.G.

Flange for connecting to ductwork or air handlers

Flat Bank ASHRAE Housing

The Flat Bank air filter housing is designed to accommodate ASHRAE-rated air filters of different types and efficiencies. Flat Bank Housings are available in 8-1/2" deep single stage and 12" deep multi stage configurations. Single stage units can house either a 2" or 4" standard filter. The multi stage units can house 2 filter stages with standard filters of 2" and 4" depth.

Standard Flat Bank Housings are fabricated from galvanized steel, but can be ordered in stainless steel. The housings are intermittently welded and caulked to prevent air bypass. The unit features a one-piece construction with a gasketed U-channel extrusion to secure the filters, and upstream corner supports to increase the overall rigidity of the housing.

When used with 4" deep filters, the Flat Bank Housing can operate at face velocities up to 625 FPM. Flat Bank Housings are available in sizes ranging up to 8' high by 8' wide in nominal filter area. Quick opening access doors allow for the servicing of the filters.

Using the included flange, Flat Bank Housings can be installed in locations where space limitations exist. For example, in a duct or next to an air handling unit.

Flat Bank Housings can be made utilizing a large number of options, meaning housings can be customized to meet a variety of application-specific requirements.

Options

- Weather cover
- Double Wall Insulation
- Lifting lugs
- Flanges to connect to existing air handlers
- Stainless Steel Construction
- Static taps or magnehelic gages

Flat Bank ASHRAE Housing

		Width Code - Overall Unit Width								
		05W 14- 1/8"	10W 26-1/8"	15W 37-1/2"	20W 49-1/2"	25W 60-7/8"	30W 72-7/8"	35W 84-1/4"	40W 96-1/4"	
Height Code - Unit Overall Height	05H 14-7/8"	Capacity (CFM)	500	1000	1500	2000	2500	3000	3500	4000
		Face Area (ft ²)	1	2	3	4	5	6	7	8
	10H 26-7/8"	Capacity (CFM)	1000	2000	3000	4000	5000	6000	7000	8000
		Face Area (ft ²)	2	4	6	8	10	12	14	16
	15H 39"	Capacity (CFM)	1500	3000	4500	6000	7500	9000	10500	12000
		Face Area (ft ²)	3	6	9	12	15	18	21	24
	20H 51"	Capacity (CFM)	2000	4000	6000	8000	10000	12000	14000	16000
		Face Area (ft ²)	4	8	12	16	20	24	28	32
	25H 63-1/8"	Capacity (CFM)	2500	5000	7500	10000	12500	15000	17500	20000
		Face Area (ft ²)	5	10	15	20	25	30	35	40
	30H 75-1/8"	Capacity (CFM)	3000	6000	9000	12000	15000	18000	21000	24000
		Face Area (ft ²)	6	12	18	24	30	36	42	48
	35H 87-1/4"	Capacity (CFM)	3500	7000	10500	14000	17500	21000	24500	28000
		Face Area (ft ²)	7	14	21	28	35	42	49	56
	40H 99-1/4"	Capacity (CFM)	4000	8000	12000	16000	20000	24000	28000	32000
		Face Area (ft ²)	8	16	24	32	40	48	56	64

*Listed capacity assumes a 500 FPM housing approach airflow velocity